

Osprey[®]

Video

Osprey[®] HSC-2

Mini HDMI to 3G SDI Converter

USB powered HDMI to SDI Converter

This non-scaling Osprey HDMI to SDI Converter with Automatic Input Detection will accept any HDMI input up to 1080P60 and passes it to Dual 3G SDI Outputs.



SDI Compliance

SMPTE 259M, SMPTE 292, SMPTE 424M

HDMI Color Space and Precision

YUV 4:2:2, YUV 4:4:4, RGB 4:4:4

Input

1x HDMI (Type A – Full Size)

Outputs

2x 3G / HD / SD SDI (Full Size BNC)

SDI Color Space and Precision

YUV 4:2:2

Supported Resolutions

1080p:60/59.94/50
1080p: 30/29.97/25/24/23.98
1080i: 60/59.94/50
1035i: 60/59.94/50
720p: 60/59.94/50
NTSC 480i / PAL 576i

LED indicators

Power
SDI Signal lock

Dimensions

3.54" L x .87" H x 1.57" W (90mm L x 22mm H x 40mm W)

Power Connector

Micro USB

Power

+5 VDC @ 2W
May be powered by USB charger, PC or portable battery pack

Warranty

2 years limited hardware warranty

Compliance

CE, FCC, ROHS, WEEE

In the Box

HDMI to SDI Converter
USB Wall Power Supply
Mounting bracket
USB cable

20161024

© 2016 Osprey Video. Osprey®, SimulStream® and Ceylon® are registered trademarks of Osprey Video AG. All other trademarks are the property of their respective owners. Product specifications and availability may change without notice.

North America 800 251 7900 | Europe / Africa/ Asia / Middle East +1 800 251 7900 | www.ospreyvideo.com