

# Osprey<sup>®</sup>

## Video

### Osprey<sup>®</sup> SHC-2

Mini 3G SDI to HDMI Converter

#### USB powered SDI to HDMI Converter

This non-scaling Osprey SDI to HDMI Converter with Automatic Input Detection will accept any single link SDI input up to 3G and passes it to an HDMI 1.3 Output as well as to an SDI Loopout.



#### Standards Compliance

SMPTE 259M, SMPTE 292, SMPTE 424M

#### SDI Color Space and Precision

YUV 4:2:2

#### SDI Auto Switching

Auto Detect SD, HD, 3G-SDI

#### Input

1x 3G / HD / SD SDI (Full Size BNC)

#### Outputs

1x HDMI (Type A – Full Size)

1x 3G / HD / SD SDI (Full Size BNC) Loopout

#### HDMI Color Space and Precision

YUV 4:2:2

#### Supported Resolutions

1080p:60/59.94/50

1080p: 30/29.97/25/24/23.98

1080PsF: 30/29.97/25/24/23.98

1080i: 60/59.94/50

1035i: 60/59.94/50

720p: 60/59.94/50

NTSC 480i / PAL 576i

#### LED indicators

Power

SDI Signal lock

#### Dimensions

3.54" L x .87" H x 1.57" W (90mm L x 22mm H x 40mm W)

#### Power Connector

Micro USB

#### Power

+5 VDC @ 2W

May be powered by USB charger, PC or portable battery pack

#### Warranty

2 years limited hardware warranty

#### Compliance

CE, FCC, ROHS, WEEE

#### In the Box

SDI to HDMI Converter

USB Wall Power Supply

Mounting bracket

USB cable

20161024

© 2016 Osprey Video. Osprey®, SimulStream® and Ceylon® are registered trademarks of Osprey Video AG. All other trademarks are the property of their respective owners. Product specifications and availability may change without notice.

North America 800 251 7900 | Europe / Africa/ Asia / Middle East +1 800 251 7900 | [www.ospreyvideo.com](http://www.ospreyvideo.com)